

SEMI AERIAL STOCK ORDER PICKER

Specification		0327	0330	0340	0345
Max. Platform Height	mm	2700	3300	4000	4500
Max. Machine Height	mm	4020	4900	5400	6100
Ground Clearance	mm	35	35	35	35
S.W.L	kg	200	200	200	200
Platform Size	mm	630×620	630×620	630×620	630×620
Lifting motor	v/kw	12/1.6	12/1.6	12/1.6	12/1.6
Battery	v/Ah	12/120	12/120	12/120	12/120
Charger	v/A	12/15	12/15	12/15	12/15
Overall Length	mm	1300	1300	1300	1300
Overall Width	mm	840	840	840	840
Overall Height	mm	1760	2040	1810	1980
Up speed	s	16	22	28	34
Down speed	s	14	16	18	20
Overall Weight	kg	290	350	410	450

The factory reserve the rights to change the material and technical specifications. Pls confirm before order.



03



Control box



Convenient maintenance

SELF-PROPELLED AERIAL STOCK ORDER PICKER

Specification		T0330	T0335	T0340	T0345
Max. Platform Height	mm	3000	3500	4000	4500
Max. Machine Height	mm	4439	5189	5400	6000
Ground Clearance	mm	40			
S.W.L	kg	300			
Platform Size	mm	650×690			
Max driving speed(fall)	km/h	4			
Max driving speed(rise)	km/h	1.5			
Min turning Radius	mm	1500			
Max adapted ground degree	%	15~20			
Driving Wheel Size	mm	φ230×80			
Caster Size	in	6			
Driving Motor	v/kw	2×24/0.4			
Lifting Motor	v/kw	24/1.6			
Maintenance free battery	v/Ah	2×12/120			
Charger	v/A	24/20			
Overall Length	mm	1520			
Overall Width	mm	760			
Overall Height	mm	1860	2110	1810	1990
Overall Weight	kg	580	600	662	682

The factory reserve the rights to change the material and technical specifications. Pls confirm before order.



Emergency drop valve



Operating handle



Battery cover plate



04

