

## High Lifting Pallet Truck

- \* Ideal design, pallet truck with the numerous possibilities makes this unit very suitable as pallet truck / scissor lift table.
- \* Supports legs come in to operation automatically. It prevents the unit from moving when the forks are raised to keep the safety of the operator.
- \* Truck automatically shows the descending speed when heavy goods loaded to help prevent cargo damage.
- \* 210 degree turning radius.
- \* 2 lateral stabilizers ensure good stability when raised.

## Stainless Steel Pallet Truck

Material: Grade 316

All parts are made of stainless including hydraulic pump, fork frame, handle, push rod, bearing, pin and bolt, Etc...

For use in meat and other food industry, dairy canning and all areas where corrosive acids and saline solutions are used.

Rollers/Wheels: Nylon. 75mm(3") lowered fork height available.

| Model               |    | AFZA-27      | AFZA-27G     | AFZA-27SS    |
|---------------------|----|--------------|--------------|--------------|
| Capacity Q          | Kg | 1000         | 1000         | 1000         |
| Min. Fork Height    | mm | 85           | 85           | 85           |
| Max. Fork Height    | mm | 800          | 800          | 800          |
| Size of Fork        | mm | 162 x 50     | 162 x 50     | 162 x 50     |
| Steering Wheel      | mm | Dia 150 x 50 | Dia 150 x 50 | Dia 150 x 50 |
| Load Roller Tandem  | mm | Dia 74 x 50  | Dia 74 x 50  | Dia 74 x 50  |
| Width overall Forks | mm | 550          | 550          | 550          |
| Fork Length         | mm | 1150         | 1150         | 1150         |
| Net Weight          | kg | 112          | 112          | 110-125      |



## High Lifting Pallet Truck-Electric

- \* Designed to lift open bottom skids, boxes and baskets.
- \* Side stabilizers provide balance to the unit when the load is lifted.
- \* Two operations available -- Hand Pump and 12V DC Power with rocket switch to raise and lower.
- \* Hand Pump design features an ergonomic pump handle with 2 lifting speeds to accommodate for light or heavy loads.
- \* Suffix "SS" for stainless steel construction.

| Model                 |      | AFZA-27E     |
|-----------------------|------|--------------|
| Capacity Q            | Kg   | 1000         |
| Min. Fork Height      | mm   | 85           |
| Max. Fork Height      | mm   | 800          |
| Size of Fork          | mm   | 160 x 50     |
| Steering Wheel        | mm   | Dia 180 x 50 |
| Load Roller Tandem    | mm   | 74 x 50      |
| Width overall Forks   | mm   | 540/680      |
| Fork Length           | mm   | 1170         |
| Battery (5h autonomy) | V/Ah | 12/60        |
| Lifting Motor Power   | kw   | 0.8          |
| Net Weight            | kg   | 169          |

