

Low Profile Pallet Truck



Min. Height: 36mm, 55mm only!

For super low pallet.
Conforms to EN1757-2.

Rollers: Polyurethane
Wheels: Nylon, Polyurethane, Rubber.

Model	HPL20S	HPL20L	HPM10S	HPM10L
Type	Low Profile		Super Low	
Capacity (kg)	2000	2000	1000	1000
Min. Fork Height (mm)	55	55	36	36
Max. Fork Height (mm)	170	170	95	95
Width over Forks (mm)	540	680	540	680
Fork Length (mm)	1150	1220	1150	1220
Net Weight (kg)	75	79	70	74

Four Way Pallet Truck



Extra support legs for balancing!

Capacity:

2000kg at fork height from 85 to 175mm.
1200kg at fork height from 185 to 205mm.

Unique 4-directional movement capacity provides the flexibility to maneuver wide loads through standard aisles.

An additional set of wheels allows pallet truck to be moved sideways in addition to be the conventional forward and back directions.

Move heavy loads, quickly and effortlessly, with convenient hydraulic power and industrial quality features.

Trucks are constructed of 4mm thick steel with reinforced fork bracing.

Include sealed ball bearings on wheels that are permanently lubed and polyurethane coated.

Handle has a cushion grip with a 3-position lever.



Front load rollers.

Model	Capacity	Min. /Max. Fork Height	Fork Size		Rear Wheel	Net Weight
			Length	Width Over Forks		
HPF12S	2000/1200kg	85/205mm	1150mm	540mm	200 mm	75kg
HPF12L	2000/1200kg	85/205mm	1150mm	680mm	200 mm	78kg