

Hydraulic Manual Stacker

- * The hydraulic pump uses the newest technology
- * Special C-shaped steel helps provide strength and rigidity
- * Option adjustable forks for wider applications
- * Save time and manpower

The standard machine is available upto a lift height of 1600mm.
An option upto 4200 mm is also available.



Model		AMS-5-16	AMS-10-16	AMS-15-16	AMS-20-16
Capacity Q	Kg	500	1000	1500	2000
Mast Type		Mono	Mono	Mono	Mono
Min. Fork Height H1	mm	90	90	90	90
Max. Fork Height H2	mm	1600	1600	1600	1600
Mast Lowered Height	mm	2080	2080	2080	2080
Width overall Forks	mm	560	560	560	560
Fork Length	mm	1150	1150	1150	1150
Weight	kg	155	250	275	250

Steering Wheel:

2 Nylon Wheel Dia 180 x 50mm

Load Wheel:

4 Nylon Wheel Dia 85 x 70mm

Semi Electric Stacker-Wider Leg

- * Heavy duty design with quality mast construction.
- * Drop forged forks.
- * Straddle leg design suitable for two faces or low pallet.
- * Safety guard on load roller and steering wheel.
- * Light and easy manual steering system.
- * High quality trouble free power pack.

The standard machine is available upto a lift height of 1600mm. An option upto 4 2 0 0 m m i s a l s o Available.

Model		ASES-5W	ASES-10W	ASES-15W
Capacity	kg	500	1000	1000
Load Center	kg	500	500	500
Mast	mm	Mono	Mono	Mono
Min. Fork Height	mm	65	65	65
Max. Lift Height "B"	mm	1600	1600	1600
Shut Height "A"	mm	2080	2080	2080
Fork Length	mm	1000	1000	1000
Fork Width (Adjustable)	mm	230-790	230-790	230-790
Leg Width (Inside)	mm	1270	1270	1270
Power Unit	w	1500	1500	1500
Battery	v/ah	12/120	12/120	12/120
Overall Dimensions	mm	1674x1502x290	1674x1502x290	1674x1502x290
Weight Without Battery	kg	482	502	532

